





Reducers – ABRE Range

Applications

- Flameproof Ex d and Increased Safety Ex e
- For connection between cable entry devices having dissimilar threads
- Male and female threads, both Metric and NPT
- ATEX Certificate Number - Baseefa09ATEX0188X
IECEX Certificate Number - IECEX BAS 09.0090X



		FEMALE THREAD																							
		METRIC																							
MALE THREAD	METRIC	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"			
	M16																								
	M20																								
	M25																								
	M32																								
	M40																								
	M50																								
	M63																								
	M75																								
	M80																								
M90																									
M100																									
NPT	1/2"																								
	3/4"																								
	1"																								
	1 1/4"																								
	1 1/2"																								
	2"																								
	2 1/2"																								
	3"																								
	3 1/2"																								
	4"																								

Protection

II 2 GD Ex db IIC Gb / Ex eb IIC Gb, Ex tb IIIC Db
Suitable for use in Zone 1, Zone 2, Zone 21 & Zone 22
IP66 to IEC 529
Operational temperature range: -60°C to +100°C

Material

Nickel plated brass or Stainless Steel 316(L)

Accessories

Locknut, sealing washer, serrated washer and earth tag are available

